

## P-70 PORTABLE POWER PACK UNIT



### GENERAL DESCRIPTION

The Magnaflux<sup>®</sup> Portable Power Packs are convenient and economical inspection units that are used in a wide range of magnetic particle applications that require only moderate power. They are ideal for large or heavy parts, in-service mobile equipment or job-site welds.

### BENEFITS

- Find surface defects with AC current; switch cable connection to half wave DC (HWDC) for near-surface flaws
- Locate defects in any direction using prods, central conductor, coil (wrap part with 3-5 turns of cable)
- Infinitely variable current control
- Demagnetize your parts in AC mode by slowly turning the current dial to zero
- Built-in automatic-reset circuit breaker
- May be used as the main power source for the Magnaflux MAG Kit modular bench inspection system

### SPECIFICATIONS

- Length: 17.5" (44.5 cm)
- Width: 9" (22.9 cm)
- Height: 8" (20.3cm)
- Maximum Output\*: 750 amps, AC or HWDC
- Current Input Single Phase: 115/230 Volts, 50/60 Hertz, single phase power
- Line Current: 26 amps @ 115 VAC; 13 amps @ 230 VAC
- Maximum Duty Cycle: 2 minutes ON, 2 minutes OFF
- Unit Weight: 35 lbs. (15.9 kg)

**Note:** Current ratings are based on the use of two 15-foot length of 4/0 Cable

**ACCESSORIES AND CABLES FOR START-UP**

- Cable 4/0, 15 ft. with either ends at both ends (Part Number 11308)
- Remote palm button cable, 15 ft. (Part Number 169621)
- Powder spray bulb w/aluminum head (Part Number 501232)
- Pie field indicator (Part Number 169799)
- Pump assembly, 5 gallon, 115 volt (Part Number 69390)
- Either end lug adaptor, changes lug terminals to either end terminals

<b>UNIT COMPARISON CHART</b>		
	<b>MODEL P-70</b>	<b>MODEL P-1500</b>
<b>DIMENSIONS</b>	17.5"L x 9"W x 8"H 44.5 x 23 x 19.1 cm	22"L x 9.5"W x 9.5"H 55.8 x 24.3 x 24.3 cm
<b>WEIGHT</b>	35 lbs. (15.9 kg)	93 lbs. (42.2 kg)
<b>MAX OUTPUT<sup>1</sup></b>	750 Amps AC or HWDC	1500 Amps AC or HWDC
<b>CURRENT OUTPUT<sup>2</sup> (single phase)</b>	115 VAC 50/60 Hz 230 VAC 50/60 Hz	230 VAC 50/60 Hz 460 VAC 50/60 Hz
<b>LINE CURRENT</b>	26 Amps @ 115 VAC 13 Amps @ 230 VAC	42 Amps @ 230 VAC 21 Amps @ 460 VAC
<b>MAX DUTY CYCLE</b>	2 Minutes ON 2 Minutes OFF	2 Minutes ON 2 Minutes OFF
<sup>1</sup> Current ratings based on use of two 15-foot lengths of 4/0 cable. <sup>2</sup> Other voltages available.		